



SEQ NO	QTY	Item ID	Item Name	Dimension	Standard-ID	Basic Material	Net Weight
1	1	107.390.729.500	FLANGE DIMENSIONS				0.001
Prod.	12 X92-B						
Change History							
	B	qyi101	yzh102	09.05.2022	CNAA001851	Yard Connection updated	4 3
	A	wta101	sth017	27.01.2021	EAAD095757	Legacy information. See corresponding ChangeNotice	4 3
	-	zta101	mhu019	18.08.2020	EAAD093807	Legacy information. See corresponding ChangeNotice	4 3
	Rev.	Creator	Approver	Approval Date	Change ID	Change Synopsis	Approved Activity Code E C
			PIPE CONNECTION PLAN				
Bill Of Material			Dimension				
Copyright Winterthur Gas & Diesel Ltd. All rights reserved. By taking possession of the document the recipient recognizes and honours these rights. Neither the whole nor any part of this document may be used in any way for construction, fabrication, marketing or any other purpose nor copied in any way nor made accessible to third parties without the previous written consent of Winterthur Gas & Diesel Ltd.			Units [m] [kg]		Basic Material		Net Weight 0.001
			Main Design Yes		Design Group 8020	Q-Code XXXXX	Standard WDS
			Qty per Engine	A4	Item ID PAAD358528	BOM Page/s	01/01

Download
"DXF file"

Abgasseite
EXHAUST SIDE

Antriebsseite
DRIVING END

<i>Gasaustritt-Stellung</i> GAS OUTLET POSITION	<i>x</i>	<i>y</i>
 α		
0°	4170	10355
15°	4416	10323
30°	4645	10228
45°	4842	10077

- *1) Optionale Ausführung (wenn verlangt)
OPTIONAL EXECUTION (IF REQUIRED)
- *2) Standard Ausführung
STANDARD EXECUTION
Vorschlag, endgültige Position in Übereinstimmung mit Werft zu bestimmen
PROPOSAL TO DETERMINE FINAL POSITION IN ACCORDANCE WITH SHIPYARD
- *3) Nur bei Ausführung mit separatem Brennstoff-pumpen-Ölkreislauf
ONLY FOR EXECUTION WITH SEPARATE LUBRICATING OIL FOR FUEL PUMPS
- *4) SEE DG 9722
- *5) SEE DAAD116127 (A)

Alle Flanschanschlüsse am Motor sind mit Gegenflanschen versehen (Blindflansch), ausgenommen der Anschluss fuer den Gasaustritt am Turbolader. Die Blindflansche sind nach dem betreffenden Rohrdurchmesser des Werftanschlusses aufzubohren. THE PIPE CONNECTIONS ON THE ENGINE ARE SUPPLIED WITH WATING FLANGES (BLIND), WITH EXCEPTION OF THE TURBO-CHARGER EXHAUST GAS OUTLET. BLIND FLANGES TO BE DRILLED TO MATCH PIPE DIA SUPPLIED BY THE SHIPYARD.

Die Gewinde-Anschlüsse werden komplett geliefert
SCREWED CONNECTIONS ARE SUPPLIED COMPLETE

3x MET71MB

DIMENSIONS FOR REFERENCE ONLY.
TECHNICAL MODIFICATIONS RESERVED.
LATER ADAPTATIONS ARE POSSIBLE BASED ON PROJECT REQUIREMENTS AND RELATED DETAIL DESIGN. THIS PIPE CONNECTION PLAN MAY NOT BE USED FOR FINAL DESIGN!

New design for reduced oil pan height will be introduced for 12X92-B engine.

Externes TL Oelsystem
EXTERNAL TC OIL SYSTEM (A)

Brennstoffseite
FUEL SIDE

Freies Ende
FREE END

Freies Ende
FREE END

Antriebsseite
DRIVING END

12X92-B									
Change History	B	qy101	ych102	09.05.2022	CHM001051	Yard Connection updated			4 3
	A	wfa101	stf1017	27.01.2021	EAAD095957	Legacy information. See corresponding ChangeNotice			4 3
	-	zta101	nhu109	18.08.2020	EAAD093807	Legacy information. See corresponding ChangeNotice			4 3
Rev.	Creator	Approver	Approval Date	Change ID	Change Synopsi	Approved		Activity Code	E C

WIN GD Winterthur Gas & Diesel		PIPE CONNECTION PLAN							
--	--	----------------------	--	--	--	--	--	--	--

separate BOM available		Dimension							
Scale	1:50	Units	[mm]	[kg]	Basic Material		Net Weight		

SURFACE PROTECTION SEE GROUP 0344		Copyright Winterthur Gas & Diesel Ltd. All rights reserved. No further dissemination of this drawing for reproduction, modification or further use is permitted without the written consent of Winterthur Gas & Diesel Ltd.		Main Design	Yes	Design Group	8020	Q-Code	XXXXX	Standard	WDS
TOLERANCING PRINCIPLE ISO8015		GENERAL TOLERANCES ACCORDING TO ISO2768-mS		Qty per	Engine	Item ID	PAAD358528		Drawing Page	1/2	


Copyright Wärtsilä. All rights reserved. By taking possession of the drawing, the recipient recognizes and honors these rights. Neither the whole nor any part of this drawing may be used in any way for construction, fabrication, marketing or any other purpose nor copied in any way nor made accessible to third parties without the previous written consent of Wärtsilä.

ISO																
6 bar							16 bar									
PN	DN	OUT.DIA.	THICK	DIM. FOR SCREWS			PN	DN	OUT.DIA.	THICK	DIM. FOR SCREWS					
6 bar	25	100	14	75	4	M10	11	16 bar	25	115	16	85	4	M12	14	
	32	120	16	90	4	M12	14		32	140	18	100	4	M16	18	
	40	130	16	100	4	M12	14		40	150	18	110	4	M16	18	
	50	140	16	110	4	M12	14		50	165	19	125	4	M16	18	
	65	160	16	130	4	M12	14		65	185	20	145	8	M16	18	
	80	190	18	150	4	M16	18		80	200	20	160	8	M16	18	
	100	210	18	170	4	M16	18		100	220	22	180	8	M16	18	
	125	240	20	200	8	M16	18		125	250	22	210	8	M16	18	
	150	265	20	225	8	M16	18		150	285	24	240	8	M20	22	
	200	320	22	280	8	M16	18		200	340	26	295	12	M20	22	
	250	375	24	335	12	M16	18		250	405	32	355	12	M24	26	
	300	440	24	395	12	M20	22		300	460	32	410	12	M24	26	
	350	490	26	445	12	M20	22		350	520	35	470	16	M24	26	
	400	540	28	495	16	M20	22		400	580	38	525	16	M27	30	
	450	595	30	550	16	M20	22		450	640	42	585	20	M27	30	
	500	645	30	600	20	M20	22		500	715	46	650	20	M30	33	
PN	DN	OUT.DIA.	THICK	DIM. FOR SCREWS			PN	DN	OUT.DIA.	THICK	DIM. FOR SCREWS					
10 bar	25	115	16	85	4	M12	14	40 bar	25	115	16	85	4	M12	14	
	32	140	18	100	4	M16	18		32	140	18	100	4	M16	18	
	40	150	18	110	4	M16	18		40	150	18	110	4	M16	18	
	50	165	19	125	4	M16	18		50	165	20	125	4	M16	18	
	65	185	20	145	8	M16	18		65	185	22	145	8	M16	18	
	80	200	20	160	8	M16	18		80	200	24	160	8	M16	18	
	100	220	22	180	8	M16	18		100	235	26	190	8	M20	22	
	125	250	22	210	8	M16	18		125	270	28	220	8	M24	26	
	150	285	24	240	8	M20	22		150	300	30	250	8	M24	26	
	200	340	24	295	8	M20	22		200	375	36	320	12	M27	30	
	250	395	26	350	12	M20	22		250	450	44	385	12	M30	33	
	300	445	26	400	12	M20	22		300	515	48	450	16	M30	33	
	350	505	28	460	16	M20	22		350	580	54	510	16	M33	36	
	400	565	32	515	16	M24	26		400	660	60	585	16	M36	39	
	450	615	38	565	20	M24	26									
	500	670	38	620	20	M24	26									

JIS

PN	DN	OUT.DIA.	THICK	DIM. FOR SCREWS			
5 bar	25	95	10	75	4	M10	12
	32	115	12	90	4	M12	15
	40	120	12	95	4	M12	15
	50	130	14	105	4	M12	15
	65	155	14	130	4	M12	15
	80	180	14	145	4	M16	19
	100	200	16	165	8	M16	19
	125	235	16	200	8	M16	19
	150	265	18	230	8	M16	19
	200	320	20	280	8	M20	23
	250	385	22	345	12	M20	23
	300	430	22	390	12	M20	23
	350	480	24	435	12	M22	25
	400	540	24	495	16	M22	25
	450	605	24	555	16	M22	25
	500	655	24	605	20	M22	25
PN	DN	OUT.DIA.	THICK	DIM. FOR SCREWS			
10 bar	25	125	14	90	4	M16	19
	32	135	16	100	4	M16	19
	40	140	16	105	4	M16	19
	50	155	16	120	4	M16	19
	65	175	18	140	4	M16	19
	80	185	18	150	8	M16	19
	100	210	18	175	8	M16	19
	125	250	20	210	8	M20	23
	150	280	22	240	8	M20	23
	200	330	22	290	12	M20	23
	250	400	24	355	12	M22	25
	300	445	24	400	16	M22	25
	350	490	26	445	16	M22	25
	400	560	28	510	16	M24	27
	450	620	30	565	20	M24	27
	500	675	30	620	20	M24	27

PN	DN	OUT.DIA.	THICK	DIM. FOR SCREWS			
16 bar	25	125	14	90	4	M16	19
	32	135	16	100	4	M16	19
	40	140	16	105	4	M16	19
	50	155	16	120	8	M16	19
	65	175	18	140	8	M16	19
	80	200	20	160	8	M20	23
	100	225	22	185	8	M20	23
	125	270	22	225	8	M22	25
	150	305	24	260	12	M22	25
	200	350	26	305	12	M22	25
	250	430	28	380	12	M24	27
	300	480	30	430	16	M24	27
	350	540	34	480	16	M30	33
	400	605	38	540	16	M30	33
	450	675	40	605	20	M30	33
	500	730	42	660	20	M30	33
PN	DN	OUT.DIA.	THICK	DIM. FOR SCREWS			
30 bar	25	130	20	95	4	M16	19
	32	140	22	105	4	M16	19
	40	160	22	120	4	M20	23
	50	165	22	130	8	M16	19
	65	200	26	160	8	M20	23
	80	210	28	170	8	M20	23
	100	240	32	195	8	M22	25
	125	275	36	230	8	M22	25
	150	325	38	275	12	M24	27
	200	370	42	320	12	M24	27
	250	450	48	390	12	M30	33
	300	515	52	450	16	M30	33
	350	560	54	495	16	M30	33
	400	630	60	560	16	M36	39

Substitute for:										PC	Q-Code	X	X	X	X	X
Modif	A	EAAD084180	04.10.2012													
		Number	Drawn Date		Number	Drawn Date		Number	Drawn Date		Number	Drawn Date				
		Product W-2S				Flange Dimensions										
Made	19.09.2007	N. Brand			Main Drw.	Page 1 / 1	Material ID 107.390.729.500									
Chkd	27.09.2007	M. Frei			Design Group	Drawing ID 107.390.729										Rev A
Appd	27.09.2007	B. Haag			8020											

WinGD-12X92-B _Pipe Connection Plan

TRACK CHANGES

DATE	SUBJECT	DESCRIPTION
2020-09-02	DRAWING SET	First web upload
2021-03-16	DAAD131350	Revised Pipe connection plan for 3xMET71 MB has been updated.
2022-05-25	PAAD358528	Revised Pipe connection plan for 3xMET71 MB has been updated.

DISCLAIMER

© Copyright by Winterthur Gas & Diesel Ltd.

All rights reserved. No part of this document may be reproduced or copied in any form or by any means (electronic, mechanical, graphic, photocopying, recording, taping or other information retrieval systems) without the prior written permission of the copyright owner.

THIS PUBLICATION IS DESIGNED TO PROVIDE AN ACCURATE AND AUTHORITATIVE INFORMATION WITH REGARD TO THE SUBJECT-MATTER COVERED AS WAS AVAILABLE AT THE TIME OF PRINTING. HOWEVER, THE PUBLICATION DEALS WITH COMPLICATED TECHNICAL MATTERS SUITED ONLY FOR SPECIALISTS IN THE AREA, AND THE DESIGN OF THE SUBJECT-PRODUCTS IS SUBJECT TO REGULAR IMPROVEMENTS, MODIFICATIONS AND CHANGES. CONSEQUENTLY, THE PUBLISHER AND COPYRIGHT OWNER OF THIS PUBLICATION CAN NOT ACCEPT ANY RESPONSIBILITY OR LIABILITY FOR ANY EVENTUAL ERRORS OR OMISSIONS IN THIS BOOKLET OR FOR DISCREPANCIES ARISING FROM THE FEATURES OF ANY ACTUAL ITEM IN THE RESPECTIVE PRODUCT BEING DIFFERENT FROM THOSE SHOWN IN THIS PUBLICATION. THE PUBLISHER AND COPYRIGHT OWNER SHALL UNDER NO CIRCUMSTANCES BE HELD LIABLE FOR ANY FINANCIAL CONSEQUENTIAL DAMAGES OR OTHER LOSS, OR ANY OTHER DAMAGE OR INJURY, SUFFERED BY ANY PARTY MAKING USE OF THIS PUBLICATION OR THE INFORMATION CONTAINED HEREIN.